

Kubota

 Power



MODEL

RKYSTD 15KB

 Standby
15 kW

 60
Hz

 1800
RPM

 EPA
Tier4

Soundproof Generator



Referential Image

RATINGS

Voltage (Ph-Ph/Ph-L)		240/120V
Phase		1PH
Power factor	Cos Phi	1
Frequency	Hz	60
Controlator	Deep Sea	6320 MKII
Engine	Kubota	D1703-M-E3BG-KEA-2
Alternator	Stamford	SOL2-G
Leads Connection		4 Lead Series

STANDBY

Power	kW	15
Power	kVA	15
Amperage	A	62.4

PRIME

Power	kW	12
Power	kVA	12
Amperage	A	50

Certifications and Standards

- EPA Tier 4 (Refers to engine emissions control)
- IBC 2018 / ASCE/SEI 7-16 - optional (Refers to seismic and wind safety of generator)
- UL 2200 - optional (Refers to the generator assembly)
- UL 142 - optional (Refers to the design, construction, and testing of the tank)
- ISO 8528-5 - optional (Refers to testing for transient response)
- Verified product design, quality, and performance integrity
- All generator systems are prototype and factory tested

Warranty

- 2 years or 2000 hours operational warranty

Prime Power (PRP): According to ISO 8528-1:2018, PRP is the maximum power available for use under variable loads for an unlimited number of hours per year within the manufacturer's prescribed maintenance intervals and under the environmental conditions specified by the manufacturer. The average power consumed over a 24-hour period must not exceed 70% of the PRP.

Emergency Standby Power (ESP): According to ISO 8528-1:2018, ESP is the maximum power available for use under variable loads in the event of a grid power outage or during testing conditions for a limited number of hours per year, specifically 200 hours, within the manufacturer's prescribed maintenance intervals and under the environmental conditions specified by the manufacturer. The average power consumed over a 24-hour period must not exceed 70% of the ESP.

Continuous Power (COP): According to Standard ISO 8528-1:2018, this is the maximum power available for continuous loads for unlimited running hours a year between the maintenance times recommended by the manufacturer under the environmental conditions established by the same.

Application Data

ENGINE

Manufacturer	Kubota	Displacement	L(in3)	1.65(101)
Model	D1703-M-E3BG-KEA-2	Bore x stroke	mm(in)	87x92.4(3.43x3.64)
Configuration	3 cylinders in line	Frequency	Hz	60
Governor isochronous	mechanical	Speed	RPM	1800
Certification EPA	Tier 4	Compression ratio		22.6:1

FUEL SYSTEM

Fuel suction fitting	5/16" NPT Female
Fuel return fitting	3/16" NPT Female
Injection type	Indirect
Recommended fuel	Diesel # 2 - ULSD

AIR REQUIREMENTS

Intake airflow	m3/min(CFM)	1.74(61.5)
Airflow for radiator	m3/min(CFM)	1.66(46.8)
Type aspiration		Natural Aspiration

LUBRICATION SYSTEM

Total oil capacity	L (gal)	5.7(1.5)
Recommended oil		SAE 15W-40

EXHAUST SYSTEM

Back pressure	kPa (in. H2 O)	10.2(40.8)
Exhaust Gas Flow	m3/min (CFM)	4.76(168)
Gas temp. (stack)	°C (°F)	510(950)

COOLING SYSTEM

Coolant capacity	L (gal)	5.5(1.5)
Ambient Temp. Rad.	°C (°F)	50(122)
Recommended coolant		50/50

ELECTRIC SYSTEM

Starting system	Volt	12
-----------------	------	----

FUEL CONSUMPTION

		STANDBY
At 100% load	L/hr (gal/hr)	4.85(1.28)
At 75% load	L/hr (gal/hr)	3.48(0.92)
At 50% load	L/hr (gal/hr)	2.58(0.68)



Alternator Specifications


GENERAL INFORMATION

Manufacturer	Stamford
Models	SOL2-G
Design	4 Poles IP23
Temp. Rise Insulation Type	Standby 150/40°C Class H
Exciter system AVR	Self Excited AS540 (+/-1%)



Control Panel Specifications

DSE6320 MKII is an Auto Start Control Module and is an Auto Mains (Utility) Failure Control Module suitable for a wide variety of single, diesel or gas, gen-set applications. Featuring a new Dual Core main processor and extended memory, the module provides faster and more powerful processing power, returning faster operational responses on intensive applications and increased functionality, with data logging facility. Monitoring an extensive number of engine parameters, the module will display warnings, shutdown and engine, alternator status information on the back-lit LCD screen, illuminated LED's, remote PC's and via SMS text alerts (with external communication device).



COMPARISOR

DSE4520 MKII DSE6320 MKII DSE7320 MKII DSE8620 MKII

GENSET AND MAIN READING

Voltage between PH-PH / N-PH	Yes	Yes	Yes	Yes
PF, Hz, kVA, kW, kVAR, A	Yes	Yes	Yes	Yes

ENGINE READING AND ALARM

High coolant temperature	Yes	Yes	Yes	Yes
Low oil pressure, coolant level, fuel level	Yes	Yes	Yes	Yes
Unexpected shutdown and Stop failure	Yes	Yes	Yes	Yes
Low battery Voltage	Yes	Yes	Yes	Yes
Battery charging alternator failure	Yes	Yes	Yes	Yes
Over and under speed	Yes	Yes	Yes	Yes
Start failure and emergency stop	Yes	Yes	Yes	Yes

ALTERNATOR READING AND ALARM


Overload, Over and Under Frequency	Yes	Yes	Yes	Yes
Over, Under and Unbalanced voltage	Yes	Yes	Yes	Yes
Short circuit and reverse power	Yes	Yes	Yes	Yes

CONNECTIVITY AND PARALLEL


USB, ECU	Yes	Yes	Yes	Yes
RS232	No	No	Yes	Yes
RS485, DSENET	No	Yes	Yes	Yes
USB HOST, Ethernet RJ45	No	No	No	Yes
Parallel function	No	No	No	Yes

Dimensions, Weight and Sound Level


Level 2 | Intake Air View



Level 2 | Lateral View



Level 2 | Exhaust View



- Level 2 enclosures include sound attenuation foam (one layer).
- Enclosure manufactured in **Aluminum** with a wind rating of **170 MPH**, according to **IBC 2018** and **ASCE/SEI7-16** standards.
- Generator assembly in accordance with **UL2200 listed**.

Enclosure	Fuel Tank	Autonomy (hr)	Length (L)	Width (W)	Dimensions, in			Weight lb	Sound Level dB(A)@7m
					Height (H)	Tank (A)	Exhaust (Ø)		
Level 2	100USG	72	71	40	49	15	2	2200	63

- All measurements are approximate and are provided for estimation purposes only. Weights do not include fuel weight.
- Sound levels are measured at **23 feet (7 meters)** in accordance with **ISO 8528-10**.
- **Single Wall** Fuel Tank manufactured in **Steel**

Standard Features

ENCLOSURE

- Aluminium Material
- Stainless steel door hinges
- Stainless steel lockable handles
- Polyurethane sound-attenuating foam
- Gasketed doors
- Rain protection visor

EXHAUST SYSTEM

- Galvanneal Material
- Rain Cap (Exhaust outlet)
- Critical Grade Muffler (enclosed only)
- Stainless Steel flexible exhaust connection

FUEL TANK

- Mild Steel Material
- Mechanical Fuel Gauge
- Internal wall drainage fitting
- External wall drainage fitting
- Spare: 2" NPT male nipple
- Spare: 2" NPT Female Coupling

ALTERNATOR

- Class H insulation material
- Brushless Excitation

GENERATOR SET

- Internal Genset Vibration Isolation
- Emergency Stop Button
- Heavy Duty Battery
- Standard Factory Test
- 2 years/2000 hours operational warranty

ENGINE

- Oil Drain Valve
- Coolant Drain Valve
- Flexible Fuel Line - NPT Connection
- Air cleaner
- SAE 4-7 1/2

Configurable **Options**

GENERATOR SET

- Open Type
- Mobile Type
- Antiseismic Isolators

ENCLOSURE

- Stainless Steel Material
- Level 3 Sound Attenuation
- Removable Doors

FUEL TANK

- Stainless Steel Material
- Digital Fuel Gauge
- Low / High Fuel Alarms
- Rupture Switch
- External Main Fuel Tank
- External Daytank

EXHAUST SYSTEM

- Stainless Steel Material Muffler
- Critical Exhaust Muffler (Open Set Only)

ELECTRICAL SYSTEM

- Battery Charger 2 units parallel for 10A

ENGINE

- Kit Spare Parts
- Fluid Containment Pan

ALTERNATOR

- Upsize Alternator
- AVR PMG
- Heater anticondensation 120V
- AVR Digital
- Droop CT for Parallelism

CIRCUIT BREAKER

- Thermal-Magnetic: trip unit 70-100% rated
- Electronic: trip unit 40-100% rated
- Motorized Circuit Breaker for Parallelism

CONTROL SYSTEM

- DSE8620 - Parallel controller
- DSE890 - Remote Communication
- Remote Annunciator

AUTOMATIC TRANSFER SWITCH (ATS)

- Switch 100-3000A
- Enclosure NEMA 3R / Galvanneal Material
- Enclosure NEMA 4X / Stainless Steel
- Enclosure NEMA 1